

BED MEASUREMENT SHEET

1. Width of the frame from outside edge to outside edge (The width of a standard Tumbl Trak is 82.5" wide) 2. Length of frame?	79	81 82 83
3. Number of holes along ONE side of the frame?4. Is the steel on your rail angle iron or flat steel?		
	Angle Iron (L-Shape)- standard	Flat steel
5. Width of the bed from outside of d-ring to outside of d-ring (measure across the bed, preferably while the bed is not strung up).		The American Commence of the C
(A standard Tumbl Trak bed is 60" wide)		
6. Length of the bed		(
7. Does the bed have d-rings or bed bars?		(

D-Rings (standard)

Bed Bars

Gym Name :_____

8. Number of d-rings along ONE side of the bed	d+ End (if applicable)	
9. Distance between the center of one d-ring to the center of the next d-ring. ————		
	Measure from the center of one D-ring to the center of the next (should be 2.5")	
10. Do the springs have rounded hooks or tapered hooks?	Tapered Hooks Rounded TT Spring Spring Rounded Hooks	
11. Length of the springs from hook to hook.		
By signing this document you confirm these me	(Standard Tumbl Trak Springs are 6" long) easurements are complete and accurate:	
Signature	Date	
Staff Review Initials		
Date		
SO#		